

SAE 85W-140

DESCRIPTION

This is multi-grade heavy duty gear oil, contains 100% Virgin base stock, formulated with the multiple additives and blended using latest technology; provides superior lubrication for gearboxes and axle. Suitable for multi-purpose transmission oil for synchronized and non-synchronized transmission and for axle.



BENEFITS

- Significantly extended transmission life
- High anti-wear properties
- High resistance to corrosion and foaming
- High resistance to oxidation
- Excellent oxidative-thermal stability

PERFORMANCE LEVEL

- API GL-5
- MIL-L-2105D
- MAN 341

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	Visual	Dark brown
Density at 20°C, g/cm ³	ASTM D4052	0,890
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	28,5
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	420
Viscosity Index	ASTM D2270	95
Pour point, °C	ASTM D97	-15
Flash point, °C	ASTM D92	240
Copper Corrosion	ASTM D130	1a