

DIESEL SAE 15W-40

DESCRIPTION

15W-40 is an advanced mineral heavy duty diesel engine oil that is intended for the lubrication of heavy duty diesel engines, naturally aspirated or turbocharged, working under variable conditions and over wide temperature ranges.



BENEFITS

- Good anti-wear, anti-foam, anti-rust properties
- Good resistance to oxidation
- Good protection from deposits at all operating temperatures
- High viscosity index

PERFORMANCE LEVEL

- API CF-4/SG
- ACEA E2-96
- MB 228.1
- MAN 271/270
- MTU type 1

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm ³	ASTM D4052	0.880
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	14.0
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	105
Viscosity Index	ASTM D2270	135
TBN, mg KOH/g	ASTM D2896	6
Pour point, °C	ASTM D97	-30
Flash point, °C	ASTM D92	220
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1.2