

# 10 000 SAE 15W-40

## DESCRIPTION

15W-40 is formulated with mineral base stocks and additives combined to meet the requirements of naturally aspired and turbocharged diesel and gasoline passenger cars and light duty commercial vehicles.



## BENEFITS

- Good low temperature properties
- Good thermal- and oxidation stability
- High dispersancy and detergency level
- Smoother, quitter drive

## PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B3-08, A3/B4-08

## AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



## TECHNICAL PROPERTIES

| CHARACTERISTIC                                  | TEST METHOD | TYPICAL VALUE |
|---|-------------|---------------|
| Appearance                                      | Visual      | Clear         |
| Color   | ASTM D1500  | 3             |
| Density at 20°C, g/cm <sup>3</sup>              | ASTM D4052  | 0,880         |
| Kinematic viscosity, 100 °C, mm <sup>2</sup> /s | ASTM D445   | 14,8          |
| Kinematic viscosity, 40 °C, mm <sup>2</sup> /s  | ASTM D445   | 118,4         |
| Viscosity Index                                 | ASTM D2270  | 128           |
| TBN, mg KOH/g                                   | ASTM D2896  | 6,5           |
| Pour point, °C                                  | ASTM D97    | -30           |
| Flash point, °C                                 | ASTM D92    | 230           |
| Copper Corrosion                                | ASTM D130   | 1a            |
| Sulfated Ash, % m/m                             | ASTM D874   | 1,1           |