

30 000 SAE 0W-30

DESCRIPTION

0W-30 is full synthetic multigrade oil made with a proprietary blend of synthetic base stocks and fortified with a balanced additive system for maximum engine protection even under the toughest driving conditions to provide among the largest gains in fuel mileage in both gasoline and diesel (without Diesel Particulate Filter or DPF) engines.



BENEFITS

- Best cold start
- Excellent fuel economy performance
- Excellent anti-wear, anti-foam, anti-rust properties
- Protects against sludge and varnish formation

PERFORMANCE LEVEL

- API SN/SM/CF
- ACEA C2-12

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm ³	ASTM D4052	0,845
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	11
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	62
Viscosity Index	ASTM D2270	171
TBN, mg KOH/g	ASTM D2896	10
Pour point, °C	ASTM D97	-45
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1,1