

# 30 000 SAE 5W-30

## DESCRIPTION

5W-30 is full synthetic multigrade engine oil manufactured using high quality additives and base oils for use in new vehicles with modern engine technology that are specifically designed to use low viscosity motor oil for maximum fuel efficiency and superior performance for petrol and diesel engines.



## BENEFITS

- Improved fuel economy
- Excellent cold start
- Excellent anti-wear, anti-foam, anti-rust properties
- Protects against sludge and varnish formation

## PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B4-I2
- BMW LL-01
- MB 229.3/229.5
- VW 502 00/505 00
- RN 0700/RN0710

## AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



## TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm <sup>3</sup>	ASTM D4052	0,845
Kinematic viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	11
Kinematic viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	62
Viscosity Index	ASTM D2270	171
TBN, mg KOH/g	ASTM D2896	10
Pour point, °C	ASTM D97	-40
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1,1