

30 000 SAE 5W-40

DESCRIPTION

5W-40 is full synthetic multigrade engine oil designed using high quality additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. This motor oil is recommended for turbo-charged and high-powered passenger car, light duty truck, sport utility vehicle and other mobile and stationary engines.



BENEFITS

- Long-term oxidation stability
- Excellent high and low temperature performance
- Excellent anti-wear, anti-foam, anti-rust properties
- Protects against sludge and varnish formation

PERFORMANCE LEVEL

- API SN/SM/SL/CF
- ACEA A3/B4-I2
- BMW LL-01
- MB 229.3/229.5/226.5
- GM-LL-B-025
- Porsche A40
- VW 502 00/505 00
- RN 0700/0710
- PSA 871 2296

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm ³	ASTM D4052	0,845
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	14
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	85
Viscosity Index	ASTM D2270	170
TBN, mg KOH/g	ASTM D2896	10
Pour point, °C	ASTM D97	-40
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1,1