

COOLANT -36°C

DESCRIPTION

Ready-to-use cooling fluid based on MEG-DAT, recommended for all cooling circuits in modern aluminium or cast-iron engines in passenger cars, vans, heavy trucks and construction equipment. It also includes anti-cavitation, anti-calcareous and anti-foaming additives, as well as an alkaline neutralizer reserve that efficiently protects the engine, the radiator, the water pump and the cooling system.



BENEFITS

- Long-Life protection of the cooling system
- Can be used in cast iron and aluminum engines
- Excellent permanent corrosion protection
- Suitable for old and modern diesel and gasoline engines

PERFORMANCE LEVEL

- VW TL 774-D, TL 774-F
- MB 325.3
- Renault 41-01-00
- Ford ESE-M97B49-A, WSS-M97B44-D, ESD-M97B49-A
- VOLVO No.260
- OPEL GM QL 130100
- John Deere H2481, C1
- Chrysler MS 9176

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Color	Visual	Red
Density at 20°C, g/cm ³	ASTM D1122	1,077
pH value	ASTM D1287	8,1
Reserve alkalinity, ml	ASTM D1121	3,5
Freezing point, °C	ASTM D1171	-36