

SAE 75W-90

DESCRIPTION

This is semi-synthetic multi-purpose, high performance gear lubricant formulated using advanced base oils and the latest technology additive system and superior performance for synchronized or non-synchronized manual gearbox, axles and reduction gears.



BENEFITS

- Significantly extended transmission life
- High anti-wear properties
- High resistance to corrosion and foaming
- High resistance to oxidation
- Excellent oxidative-thermal stability

PERFORMANCE LEVEL

- API GL-4/5
- MIL-L-2105D
- MAN 342 M2
- ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21A

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	Visual	Dark brown
Density at 20°C, g/cm ³	ASTM D4052	0,875
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	14,5
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	110
Viscosity Index	ASTM D2270	135
Pour point, °C	ASTM D97	-42
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a