

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name KANSLER, GREASE GB EP MoS<sub>2</sub>  
Product use Multipurpose lithium grease with MoS<sub>2</sub>  
Company BLW Handel GmbH  
Address Wachtelstr. 13 12526 Berlin, Deutschland  
Phone +49 30 818 78 777  
E-mail address info@kansler.de  
Emergency telephone number 112

## 2. HAZARDS IDENTIFICATION

Classification of a mixture Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008. This mixture is not classified as dangerous according to Directive 67/548/EEC.

Label elements The product does not need to be labelled in accordance with EC directives or respective national laws.

Precautionary Statements P102 Keep out of reach of children.  
P262 Do not get in eyes, on skin, or on clothing.  
P273 Avoid release to the environment.  
P281 Use personal protective equipment as required.  
P501 Dispose of contents/container to authorized collecting centers.

Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 3. COMPOSITION/INFORMATION ON INGREDIENT

Description	Mixture		
Name	W (%)	CAS Nr. EC Nr.	Classification
Lithium 12-hydroxystearate	10-20	7620-77-1 231-536-5	Not Classified

Mineral oil contains DMSO-Extract <3% (w/w) according to IP 346  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

Description of first aid measures:  
After ingestion If swallowed, get immediate medical attention. Do not induce vomiting.

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



After inhalation	Move a person to fresh air if necessary.
In case of skin contact	Wash the skin with soap and water. Remove contaminated clothing as soon as possible. Seek medical advice if symptoms persist
In case of eye contact	Flush immediately with water for at least 15 minutes. Get medical advice if discomfort continues. Continue to flush during transport to physician.
Most important symptoms and effects, both acute and delay: Symtoms/Injuries	Risk of thermal burns on contact with hot oil.
Symptoms/injuries after inhalation	May cause irritation to the eyes, nose, throat, and skin. Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation. Possible respiratory damage following repeated or prolonged inhalation.
Symptoms/injuries after skin contact	May cause moderate irritation. Risk of thermal burns on contact with molten product. Prolonged or repeated contacts with the skin may cause dermatitis. Skin rash/inflammation. Drying up of the skin.
Symptoms/injuries after eye contact	May cause moderate irritation, including burning sensation, tearing, redness or swelling.
Symptoms/injuries after ingestion	Ingestion of large amounts may produce some discomfort and gastrointestinal disturbances including a laxative action.
Indication of any immediate medical attention and special treatment needed: First aid kits	Clean, warm water, soap, drinking water.

## 5. FIREFIGHTING MEASURE

Suitable extinguishing media	Carbon dioxide (CO <sub>2</sub> ), dry chemical powder, foam. Water fog. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion.
Special hazards arising from the substance or mixture	On combustion forms: Carbon dioxide. Carbon monoxide. Smokes. Hydrocarbons. Nitrogen oxides (NO <sub>x</sub> ). Phosphorus oxides. Zinc oxide. Sulfur oxides. Material will burn but does not easily ignite. When heated above the flash point, releases vapor. Vapors can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. Mist or spray may burn at temperature below flash point.
Advice for firefighter	Wear proper protective equipment. Extra personal protection: complete protective clothing including self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures	Stop leak if safe to do so. Evacuate personnel to a safe area. Avoid any direct contact with the product. Avoid contact with skin, eye and clothing. Avoid breathing dust. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Spilled material may present a slipping hazard. Prevent entry to sewers and public waters. Wear suitable protective clothing and eye/face protection.
---	---

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



Environmental precaution Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

Methods and material for containment and cleaning up Wear suitable protective clothing. Stop leak if safe to do so. Spilled material may present a slipping hazard. Small spills: Clean up any spills as soon as possible, using an absorbent material to collect it. Contain large spills to maximize product recovery or disposal. Substance floats in water. Specialist clean-up methods may be required. Comply with applicable regulations.

Reference to other section Refer to sections 1 (contact and emergency phone number), 8 and 13.

## 7. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

Precautions for safe handling Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Conditions for safe storage, including any incompatibilities Technical measures: Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources.

Storage condition(s): Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Do not store near oxidizing agents.

Recommended Materials For containers or container linings, use mild steel or high density polyethylene.

Specific end use No additional information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters: Mineral oil TWA (ACGIH) 5 mg/m<sup>3</sup>  
Mineral oil STEL (ACGIH) 10 mg/m<sup>3</sup>

Personal protective equipment: Respiratory protection No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours.

Hand protection Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

## Skin and body protection

When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection must be worn. Wash contaminated clothing before reuse.

## Eyes/face protection

Safety glasses with side-shields. Use splash goggles when eye contact due to splashing is possible. Wear goggles and face shield if material is heated above 51°C.

## Hygiene measure

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Wash hands thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. DO NOT use gasoline, kerosene, solvents, or harsh abrasives as skin cleansers. Remove all contaminated clothing and footwear. Wash contaminated clothing prior to re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Consistent
Odor	Slight hydrocarbon
Odor Threshold	Not applicable
pH	Not applicable
Melting Point / Freezing Point	Not applicable
Initial Boiling Point and Boiling Range	Not applicable
Flash point	240°C (COC)
Flammability	Not applicable
Upper/Lower Flammability or Explosive Limits	Not applicable
Vapor Pressure@ 20 °C	<0.01 kPa
Vapor Density	>5 (air = 1)
Relative Density@ 15 °C	Not applicable
Solubility in Water	Negligible
Partition Coefficient : n-Octanol/Water	Expected to be >7
Auto-ignition Temperature	> 290 °C
Decomposition Temperature	Not applicable
Viscosity	Not applicable

## 10. STABILITY AND REACTIVITY

### Reactivity

Hazardous reactions will not occur under normal conditions.

### Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



Possibility of hazardous reaction	Hazardous polymerization will not occur.
Conditions to avoid	Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.
Incompatible materials	Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
Hazardous decomposition product	Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## II. TOXICOLOGICAL INFORMATION

### Information on toxicological effects:

#### Acute toxicity

LD50 Oral - Rat - male and female - > 5.000 mg/kg.  
(OECD Test Guideline 401)  
LC50 Inhalation - Rat - male and female - 4 h - > 5 mg/l.  
(OECD Test Guideline 403)  
LD50 Dermal - Rabbit - male.  
(OECD Test Guideline 402)

#### Skin Irritation

Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Eye Irritation

Expected to be slightly irritating.

#### Sensitization

Not expected to be a skin sensitizer.

#### Repeated dose toxicity

No data available.

#### Carcinogenicity

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractable by the IP 346 test.

#### Mutagenicity

Not expected to be mutagenic.

#### Toxicity for reproduction

Not expected to be toxic.

#### Information on likely routes of exposure: After inhalation

Inhalation of vapors may cause respiratory irritation.

#### After contact with skin

Prolonged or repeated skin contact with the material will remove natural oils and could lead to dermatitis.

#### After contact with eyes

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



Flush immediately with water for at least 15 minutes. Get medical advice if discomfort continues. Continue to flush during transport to physician.

After ingestion

Ingestion may cause nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No adverse health effects were noted.

Other information

No data available.

## 12. ECOLOGICAL INFORMATION

Toxicity

Static test LC50-Oncorhynchus mykiss (rainbow trout)->100 mg/l-96h (OECD Test Guideline 203).  
Static test LC50 - Daphnia magna (Water flea)-> 100 mg/l-48 h (OECD Test Guideline 202).

Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulative potential

Contains components with the potential to bioaccumulate.

Mobility in soil

It is to be expected small mobility in soil. Some or a few components may get into the soil and may cause pollution of ground water. Product spreads on the water surface.

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

## 13. DISPOSAL CONSIDERATIONS

Material Disposal

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

Container Disposal

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



Local Legislation

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

## 14. TRANSPORT INFORMATION

The substance is not a subject to transport regulations on hazardous goods included in ADR (road transport), RID (rail transport), IMDG (marine transport) and ICAO/IATA (air transport):

UN number	Not applicable.
UN proper shipping name	Not applicable.
Transport hazard class(es)	Not applicable.
Packing group	Not applicable.
Environmental hazards	Not applicable.
Special precautions for use	Not applicable.

## 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:  
This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Chemical safety assessment:  
For this product, a chemical safety assessment was not carried out.

## 16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3:  
Not applicable.

Key or legend to abbreviations and acronyms used in the safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

DNEL : Derived No Effect Level

EINECS : European Inventory of Existing Commercial Chemical Substances (EINECS)

EN : European Standard

ES : Exposure Scenario

EU : European Union

IATA : International Air Transport Association

LC50 : Lethal Concentration to 50 % of a test population

LD50 : Lethal Dose to 50% of a test population (Median Lethal Dose)

NDSL : Non-Domestic Substances List (NDSL)

OEL : Occupational Exposure Limit

PEC : Predicted Effect Concentration

PNEC : Predicted No Effect Concentration

PPE : Personal Protection Equipment

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

TWA : time weighted average

# MATERIAL SAFETY DATA SHEET

Revision date: 20.01.2020  
Version: 03



## Other information:

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

