

# 10 000 SAE 15W-40

## DESCRIPTION

15W-40 is formulated with mineral base stocks and additives combined to meet the requirements of naturally aspirated and turbocharged diesel and gasoline passenger cars and light duty commercial vehicles.



## BENEFITS

- Good low temperature properties
- Good thermal- and oxidation stability
- Good dispersancy and detergency level
- Smoother, quitter drive

## PERFORMANCE LEVEL

- API SJ/CF
- ACEA A3-98/B3-98

## AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



## TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm <sup>3</sup>	ASTM D4052	0.882
Kinematic viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	14.8
Kinematic viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	118.4
Viscosity Index	ASTM D2270	128
TBN, mg KOH/g	ASTM D2896	6
Pour point, °C	ASTM D97	-30
Flash point, °C	ASTM D92	230
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1.1