

10 000 SAE 20W-50

DESCRIPTION

20W-50 is formulated with mineral base stocks and additives combined to meet the requirements of naturally aspired and turbocharged diesel and gasoline passenger cars and light duty commercial vehicles.



BENEFITS

- Good low temperature properties
- Good thermal- and oxidation stability
- Smoother, quieter drive

PERFORMANCE LEVEL

- API SJ/CF
- ACEA A3-98/B3-98

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

| CHARACTERISTIC | TEST METHOD | TYPICAL VALUE |
|---|-------------|---------------|
| Appearance | Visual | Clear |
| Color | ASTM D1500 | 3 |
| Density at 20°C, g/cm ³ | ASTM D4052 | 0,880 |
| Kinematic viscosity, 100 °C, mm ² /s | ASTM D445 | 19 |
| Kinematic viscosity, 40 °C, mm ² /s | ASTM D445 | 170 |
| Viscosity Index | ASTM D2270 | 127 |
| TBN, mg KOH/g | ASTM D2896 | 6 |
| Pour point, °C | ASTM D97 | -23 |
| Flash point, °C | ASTM D92 | 230 |
| Copper Corrosion | ASTM D130 | 1a |
| Sulfated Ash, % m/m | ASTM D874 | 1,1 |