

20 000 SAE 15W-50

DESCRIPTION

15W-50 is a multipurpose multigrade semi-synthetic engine oil for all modern engine types. Effectively reduces the wear-out on all the stages of the engine burn due to the formation of a unique protective film which endures extreme loads. Prevents formation of steel particles. Has optimal low-temperature characteristics and stable viscosity during the whole used period.



BENEFITS

- Good low temperature properties
- Good thermal and oxidation stability
- High dispersency and detergency level
- High viscosity index
- Smoother, quitter drive

PERFORMANCE LEVEL

- API SN/CF
- ACEA A3/B3-12, A3/B4-12
- VW 501 01/505 00
- MB 229.1
- PSA B71 2300

AVAILABLE IN

1L, 4L, 5L, 10L, 20L, 50L, 208L, IBC, FLEXITANK



TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear
Color	ASTM D1500	3
Density at 20°C, g/cm ³	ASTM D4052	0,870
Kinematic viscosity, 100 °C, mm ² /s	ASTM D445	19
Kinematic viscosity, 40 °C, mm ² /s	ASTM D445	140
Viscosity Index	ASTM D2270	154
TBN, mg KOH/g	ASTM D2896	7,5
Pour point, °C	ASTM D97	-30
Flash point, °C	ASTM D92	225
Copper Corrosion	ASTM D130	1a
Sulfated Ash, % m/m	ASTM D874	1,1